(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 6 May 2005 (06.05.2005)

PCT

(10) International Publication Number WO 2005/03996 A1

(51) International Patent Classification⁷: B65D 41/04

(21) International Application Number:

PCT/EP2004/010636

(22) International Filing Date:

22 September 2004 (22.09.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 03022055.2

1 October 2003 (01.10.2003) EP


- (71) Applicant (for all designated States except LS, US): CROWN PACKAGING TECHNOLOGY INC [US/US]; 11535 S.Central Avenue, Alsip, Illinois 60803-2599 (US).
- (71) Applicant (for LS only): CROWN PACKAGING UK PLC [GB/GB]; Downsview Road, Wantage Oxfordshire OX12 9BP (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): DREYER, Lino

[FR/FR]; 53b rue de Riedisheim, F-68170 Rixheim (FR). GAILLOT, Maxime, Pierre, Jacques [FR/FR]; 5, Avenue du General De Gaulle, F-68300 Saint Louis (FR). ODET, Philippe, Gerard [FR/FR]; Port Riviere, 1147 Front de Saone, F-69830 St Georges de Reneins (FR). WIDMER, Sébastein, Cédric [FR/FR]; 4, Place de la Paix, F-68440 Landser (FR).

- (74) Agent: SMITH, Debra, Jane, Clare; Crown Packaging UK PLC, Downsview Road, Wantage Oxfordshire OX12 9BP (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: A CLOSURE



(57) Abstract: A plastics closure (10) for a container is provided. The closure comprises a top plate (15), with a side skirt (20) depending from the periphery thereof. A sealing strip (45) depends from the top plate (15) and is adapted to sealingly engage a container neck finish (75). The closure (10) also comprises an abutment member (55) including a guide surface (65) for guiding the sealing strip (45) towards the neck finish (75) as the closure is applied, to increase the strength of the seal. The guide surface comprises a guide member (65) which projects from the abutment member (55), thereby minimising friction between the strip (45) and the abutment member (55). The sealing strip (45) is inclined radially towards the neck finish to improve the sealing effect.

f.

WO 2005/039996 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.